

PrintMax®

Spartech's PolyPrime™ line of products offers many unique brands for a variety of applications.

BENEFITS

- UV printable – screen, digital & offset
- Economical compared to most other plastics
- Improved processing
- Superior lay-flat, sheet squareness & dimensional control
- Low minimum order size
- Custom sizes and thicknesses
- Recyclable plastic
- Excellent stiffness

PrintMax™ SPECIFICATIONS

Order Size	1000 lb min		
Appearance	White		
Gauge	0.010 - 0.187		
Opacity Range (based on 0.015G)	Translucent, opaque, double opaque, dead white		
Roll Stock	Web Width Min	1"	
	Web Width Max	60" (may vary based on gauge)	
Roll Diameter	Minimum	10"	
	Maximum	36"	
Core Size	6" standard, others available		
Sheet Stock	Width Min	12"	
	Width Max	60" (may vary based on gauge or finish)	
	Length Min	19"	
	Length Max	120"	
Surface Treat	Corona	46 dyne or higher both sides	
Surface Finish	Smooth/smooth, smooth/matte, matte/matte		

PrintMax™ TYPICAL PHYSICAL PROPERTIES

For detailed physical properties information on this branded product, please contact your sales representative or go to spartech.com to request materials.

Call 800-428-0840 or email sales@spartech.com to order these products.



1414 Crawford Drive, Crawfordsville, IN 47933 • 800-428-0840 • Fax: 800-955-0053 • www.spartech.com



Spartech is a U.S. based company.