





Acrylloy[™] Film

PRODUCT DESCRIPTION

Acrylloy $^{\mathbb{N}}$ is a modified thermoplastic acrylic resin formulated for extrusion applications. This all-acrylic resin combines the toughness of impact plastics with the exceptional transparency and UV resistance found in conventional acrylic materials.

VALUE SOLUTION

Satisfy both impact resistance and clarity requirements

With Acrylloy films, performance is achieved without sacrificing aesthetics and clarity. Custom surface colors and patterns, such as stone or marble, deliver visual appeal while the acrylic make-up of the film supplies inherent toughness and provides resistance to water and abrasion. Surfaces, such as shower or tub surrounds, are easy to clean and retain their color and clarity,

KEY CHARACTERISTICS

- High clarity—transparent, translucent or opaque
- Offers effective color stability, UV resistance and weatherability
- Provides impact toughness
- Moisture, scratch and chemical resistant
- · Laminates over PVC, ABS, PC and HIPS
- · Paintable with no priming necessary
- · Surface finishes maintained during thermoforming

TARGET MARKET AND APPLICATIONS

- Automotive interior panels and trim
- RV, travel trailer, mobile home components
- Marine dashboard, consoles, tables and enclosures
- Equipment rooftops, dashboard, consoles
- · Window profiles, shutters
- Sanitary products—shower, tub surrounds
- · Lighting diffusers
- Displays



69 Southfield Ave. Stamford, CT 06902 1-800-243-9002

www.spartech.com

Copyright ©2021, Spartech, LLC. Spartech makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Spartech makes no warranties or guarantees respecting suitability of either Spartech's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. SPARTECH MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or product reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.