

UltraTuf®

Spartech's PolyPrime® line of products offers many unique brands for a variety of applications.

BENEFITS

- UV printable – screen, digital & offset
- Excellent clarity
- High impact resistance
- Improved processing
- Superior lay-flat, sheet squareness & dimensional control
- Low minimum order size
- Custom sizes and thicknesses
- Superior die-cuttability
- Excellent stiffness

UltraTuf® SPECIFICATIONS

Order Size	2500 lb min	
Appearance	Clear	
Gauge	0.010 - 0.450	
Opacity Range (based on 0.015G)	Clear	
Roll Stock	Web Width Min	1"
	Web Width Max	48" (may vary based on gauge)
Roll Diameter	Minimum	10"
	Maximum	36"
Core Size	6" standard, others available	
Sheet Stock	Width Min	12"
	Width Max	48" (may vary based on gauge or finish)
	Length Min	19"
	Length Max	96"
Surface Treat	No treatment needed	Corona available
Surface Finish	Smooth/smooth, smooth/matte, matte/matte	
Surface Protection	Protective removable masking 1 or 2 sides	

UltraTuf® TYPICAL PHYSICAL PROPERTIES

For detailed physical properties information on this branded product, please contact your sales representative or go to spartech.com to request materials.

Call 800-677-4338 or email sales@spartech.com to order these products.



11650 Lakeside Crossing Court, Maryland Heights, MO 63146 • 800-677-4338 • www.spartech.com



Spartech is a U.S. based company.

Copyright ©2023, Spartech, LLC. Spartech makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Spartech makes no warranties or guarantees respecting suitability of either Spartech's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. SPARTECH MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or product reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.