

Floorlite C with PCR Preliminary

Flexible Sheet

Product Description

Floorlite C with PCR provides the automotive-approved TPO sheet solution developed for use in a wide range of transportation applications combined with post-consumer regrind materials for a sustainable solution. Spartech's specialty-formulated sheet incorporates 25 years of experience and expertise in the North American automotive flooring markets, and its unique physical characteristics provides customers a lightweight solution with superior toughness.

Technical Properties

| Property | Test Method | 39% PCR |
|-----------------------------|-------------|---------------------|
| Specific Gravity | ASTM D-792 | 0.92 |
| Hardness - Shore A | ASTM D-2240 | 87 |
| Tensile Strength - Die A | ASTM D-412 | 255 N MD, 255 N AMD |
| Ultimate Elongation - Die A | ASTM D-412 | 1178% MD, 1178% AMD |
| Tear Strength – Die C | ASTM D-624 | 145 N |

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**