

Royalite® R85/21

Rigid weatherable sheet

Product Description

Royalite® R85/21 thermoplastic sheet is a unique composite of Royalite® R85 low gloss weatherable cap sheet over Royalite® R21 high impact ABS substrate. It is ideal for rugged outdoor applications requiring high impact strength and stiffness. R85/21 is available in a variety of standard colors, and custom color matches also are available.

Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	1.01- 1.06
Izod Impact (Notched) 72°F	ASTM D-256	7.0 ft-lbs/in
Izod Impact (Notched) -20°F	ASTM D-256	2.0 ft-lbs/in
Tensile Strength	ASTM D-638	4,600 psi
Flexural Strength	ASTM D-790	7,500 psi
Flexural Modulus	ASTM D-790	270,000 psi
Rockwell Hardness (R Scale)	ASTM D-785	91
Heat Deflection Temperature (@264 psi - annealed)	ASTM D-648	205°F
Mold Shrinkage	Internal	0.005 - 0.007 in/in
Motor Vehicle Safety Standard	FMVSS 302	Passes

**All values based on 0.125" unless otherwise stated*

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**