

SoundX Flexible PVC A

Flexible Acoustical Barrier

Product Description

SoundX Flexible PVC A solutions provide customers with a flexible sheet for sound abatement applications. The high specific gravity of this mass-loaded solution allows SoundX Flexible PVC A to absorb sound waves and prevent the transmission of sound. SoundX Flexible PVC A is a barium-free technology with self-extinguishing flame properties. SoundX Flexible PVC A is available in UL HB-rated and RoHS-compliant formulations.

Technical Properties

Property	Test Method	Value
Specific Gravity	ASTM D-792	1.95
Hardness - Shore A	ASTM D-2240	75
Tensile Strength - Die A	ASTM D-412	MD 400 psi, A MD 400 psi
Ultimate Elongation - Die A	ASTM D-412	MD 135%, A MD 135%
Tear Strength - Die C	ASTM D-624	MD 90 psi, A MD 90 psi
Fogging	SAE J1756	80 Fn
Flammability	FMVSS 302	Pass, Self-Extinguishing

*values based on gauge range

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**