

WeatherPro SG

Performance-capped ABS Sheet

Product Description

WeatherPro SG is a rigid, UV-stable thermoplastic sheet. Combining a unique, proprietary UV-resistant surface with the ductility and high impact resistance of ABS, WeatherPro SG is ideal for thermoforming and fabrication into custom sign applications.

Technical Properties

Property	Test Method	Value*
Specific Gravity	ASTM D-792	1.11
Izod Impact (Notched) 72°F	ASTM D-256	4.0 ft-lbs/in
Tensile Strength	ASTM D-638	5,500 psi
Flexural Modulus	ASTM D-790	310,000 psi
Rockwell Hardness (R Scale)	ASTM D-785	95
Heat Deflection Temperature (@264 psi)	ASTM D-648	190°F
Falling Dart Impact 72°F	ASTM D-5420	24 ft-lbs

**All values based on 0.125" unless otherwise stated*

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**