

PRODUCT	MATERIAL	DESCRIPTION/APPLICATIONS	SPECIFICATIONS
FLAME AND SMOKE RATED SHEET			
R15	FR ABS	Fire-rated ABS rigid sheet Applications: medical and electronic device housings & components	Listed: UL 94 V-0 @ 0.060" Listed: UL 94-5VB @ 0.098"
R24	FR ABS	Economical, ABS fire-rated rigid sheet Applications: Office machine housings, medical, electronics	Listed: UL 94 HB @ 0.060"
R49/52	PVC/Acrylic	Fire-rated PVC/Acrylic sheet Applications: Building & construction, wall protection	Class-A: ASTM E-84 @ 0.080"
R52	PVC/Acrylic	Fire-rated, PVC/Acrylic sheet Applications: Electronic components & enclosures	Listed: UL 94 V-0 @ 0.027" Listed: UL 94-5VA @ 0.051" Listed: UL 94-5VB @ 0.031"
R552	PVC/Acrylic	Fire-rated, 100% recycled Applications: Medical, electronic enclosures	Listed: UL 94 V-0 @ 0.031" Listed: UL 94-5VA @ 0.094"
R57	PVC/ABS	Fire-rated PVC/ABS rigid sheet Applications: Aircraft cabin & seat components	Passes: FAR 25.853 (b) @ 0.047"
R574	FR ABS	Fire-rated Non-PVC ABS rigid sheet Applications: Medical, electronics	Listed: UL 94 V-0 @ 0.063" Listed: UL 94-5VA @ 0.125"
R59	PVC/ABS	Fire-rated PVC/ABS rigid sheet Applications: Medical, electronics, mass transit	Listed: UL 94 V-O @ 0.085" Listed: UL 94-5VA @ 0.0905"
R559	PVC/ABS	Fire-rated PVC/ABS rigid sheet, 100% recycled Applications: Aircraft cabin & seat components	Listed: UL 94 V-0 @ 0.091" Listed: UL 94-5VA @ 0.0905"
R60	PVC/Acrylic	Fire-rated PVC/Acrylic rigid sheet Applications: Aircraft cabin & seat components	Passes: FAR 25.853 (a)
R61	PVC/Acrylic	Smoke-rated, fire-rated PVC/Acrylic sheet Formulated to meet FTA Guidelines Docket 90-A Applications: Mass transit interiors, seats, panels	Passes: Motor Vehicle Standard FMVSS 302 Passes: UL 94 V-0 @ 0.031"
R926	PC/ABS	Fire-rated non-PVC rigid sheet Applications: Medical diagnostic equipment	Listed: UL 94 V-0 @ 0.059" Listed: UL 94 5VA @ 0.118"
G50	Co-polyester	Fire-rated non-PVC rigid sheet Applications: Building & construction, wall protection	Class-A: ASTM E84 @ 0.060" Class-A: ASTM G21-2015
STATIC CONTROL SHEET			
R63	PVC/ABS	Conductive, fire-rated PVC/ABS sheet Surface resistivity 10^{-5} Applications: Dissipation of electrostatic charges, IC chip carriers, trays and tray dividers	Meets: Static Decay MIL-B-81705C Meets: NFPA Code 99 Listed: UL 94 V-1 @ 0.066" & above
R632	PVC/ABS	Conductive, fire-rated PVC/ABS sheet Surface resistivity 10^{-5} Applications: Dissipation of electrostatic charges. Protects internal components from ESD in electronics. Container for explosive devices	Meets: Minimum static decay for MIL-B81705C Meets: NFPA Code 99 Listed: UL 94 V-1 @ 0.058" & above Listed: UL 94 V-0 @ 0.090" & above

PRODUCT	MATERIAL	DESCRIPTION/APPLICATIONS	SPECIFICATIONS
WEATHER RESISTANT SHEET			
R85/21	UV Cap/ABS	Rigid ABS weather-resistant sheet Applications: RV, agricultural equipment, marine parts	Passes: Motor Vehicle Standard FMVSS 302
R86	PVC/Acrylic Alloy	Weatherable, flame-retardant, rigid PVC/Acrylic Alloy Applications: Outdoor equipment housings, safety equipment, building products and signage	Listed: UL 94 V-0 @ 0.028" & above Listed: UL 94-5VA @ 0.085" & above Passes: Motor Vehicle Standard FMVSS 302
R87/59	PVC/ABS Composite	Economical, weather-resistant, fire-rated sheet Applications: Pool heaters, marine, waste and garbage containers	Listed: f1 UL 746C Listed: UL 94 V-0 @ 0.028" & above Listed: UL 94-5VA @ 0.085" & above
SPECIALTY GRADE SHEET			
HG	PVC/Acrylic	Holster grade sheet Applications: Small to medium handgun holsters, knife sheaths	Easy to form, machine, fasten and bond; durable; range of colors and textures
R26	ABS	FDA- and NSF-compliant when requested Applications: Food handling equipment and devices	Food handling trays and boxes
R52 AM	PVC/Acrylic	Fire-rated with antimicrobial technology Applications: Building & construction, wall coverings, panels	Listed: UL 94 V-0 @ 0.028" & above Listed: UL 94-5VA @ 0.118" & above Listed: UL 94-5VB @ 0.047" & above Class-A ASTM E84 @ 0.060" 100% resistance to bacterial growth Meets G-22 specs for bacterial growth
R104	ABS	Soft, vinyl foam laminated to ABS Applications: Automotive consoles, dash & door panels	RV, truck and marine parts
GENERAL PURPOSE ABS SHEET			
R12	ABS	High temperature Applications: Automotive housings & panels, food trays, tote boxes	Heat Deflection Temperature (HDT) = 220°F
R20	ABS	High impact, low temperature Applications: Water softener housings, instrument panels, luggage	Impact strength @ 72°F (ft-lb/in notch) = 8.0 Notched Izod @ (ft-lb/in notch) = 5.0
R21	ABS	High impact Applications: Office furniture, hospital beds, machine guards, housings, bus seating	Excellent, all-purpose thermoforming grade
R23	ABS	Medium impact Applications: Office or patio furniture, specialized cases	Excellent, all-purpose thermoforming grade



11650 Lakeside Crossing Ct.
Maryland Heights, MO 63146
www.spartech.com

Copyright ©2017, Spartech, LLC. Spartech makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Spartech makes no warranties or guarantees respecting suitability of either Spartech's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. SPARTECH MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or product reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.